


LED Underground light/Inground up light

with stainless steel face cover



84311/84312/84316

Outer Dimensions: Unit:mm



***Note:**

1. Item No. with "H" stands for "input voltage AC100-240V"
2. Item No. with "AS" stands for "Asymmetrical lens"
3. Any special customization, to be confirmed with us

Item No.	Light source	Lens beam angle (°)	Consumption (watt)	Input Voltage (V)	Ik rate
84311(H/AS)	1x1W LED	8°/15°/30°/45°/60°	1.2	DC12V DC24V AC100-240V	08
84312(H/AS)	1x2W LED	8°/15°/30°/45°/60°	2.6	DC12V DC24V AC100-240V	08
84316(AS)	1x3W RGB3in1 LED	30°/45°/60°	3.1	DC12V DC24V	08
84319	1x5W RGBW4in1 LED	30°/45°/60°	5.0	DC12V DC24V	08

Asymmetrical LED Inground light


with stainless steel face cover



84311AS/84312AS/84316AS

Asymmetrical lens:

CREE XPE2 / FWHM:18°28P10°



Material specifications

Housing:	Outdoor dark grey powder coated aluminum T=60-80um Adhesion of ISO class 1/ASTM class 4B
Front cover:	304# or 316#Stainless Steel
Lens:	Optical lens, efficiency≥85%
Glass:	Tempered step glass T=8mm
Glass pressure capacity:	Full area=780kgs
Gasket:	Molding shaped silicone seal
Operating temperature:	-20°C ~ 40°C
Power cable:	H05RN-F 2×0.75mm² L=0.5m(low voltage) H05RN-F 3×0.75mm² L=0.5m(for Single color/high voltage) H05RN-F 4×0.75mm² L=0.5m(for RGB)
Mounting sleeve:	ABS

