

LED underground light/Inground up light



HEX82512*SS
/stainless steel trim




HEX82512
/aluminum trim

Optional accessories

a. Asymmetrical lens



b. Honeycomb Louver



c. Plastic back box






Material specifications

Housing:	Outdoor dark grey powder coated aluminum T=60-80um Adhesion of ISO class 1/ASTM class 4B
Trim:	Stainless steel or Aluminum
Lens:	Optical lens, efficiency ≥ 85%
Glass:	Tempered step glass T=7mm
Glass pressure capacity:	Full area = 1700kgs
Gasket:	Molding shaped silicone seal
Operating temperature:	-20°C ~ 40°C
Power cable:	H05RN-F 2×0.75mm² L=0.5m (low voltage) H05RN-F 3×0.75mm² L=0.5m (for single color/high voltage)
Mounting sleeve:	ABS





Asymmetrical lens:

CREE XPE2 / FWHM: 18°×28°10°



Outer Dimensions: _____ Unit:mm



Rear view

*Note :

1. "SS" means Stainless Steel
2. Any special customized, to be confirmed

Item No.	Light source	Lens beam angle (°)	Consumption (watt)	Input Voltage (V)	Ik rate
HEX82511*SS/ HEX82511	1x1W LED	8°/15°/30°/45°/60°	1.2	DC12V/DC24V AC100-240V	08
HEX82512*SS/ HEX82512	1x2W LED	8°/15°/30°/45°/60°	2.6	DC12V/DC24V AC100-240V	08