

LED underground light/Inground up light



HE82511*SS
/stainless steel trim




HE82511
/aluminum trim

Optional accessories

a. With Diffused glass



b. Honeycomb Louver





Material specifications

Housing:	Outdoor dark grey powder coated aluminum T=60-80um Adhesion of ISO class 1/ASTM class 4B
Trim:	Stainless steel or Aluminum
Lens:	Optical lens, efficiency 285%
Glass:	Tempered step glass T=7mm
Glass pressure capacity:	Full area = 1700kgs
Gasket:	Molding shaped silicone seal
Operating temperature:	-20°C ~ 40°C
Power cable:	H05RN-F 2x0.75mm² L=0.5m (low voltage) H05RN-F 3x0.75mm² L=0.5m (for Single color/high voltage) H05RN-F 4x0.75mm² L=0.5m (for RGB)
Mounting sleeve:	ABS





Asymmetrical lens:

CREE XPE2 / FWHM: 18° 28P10°



Outer Dimensions: _____ Unit:mm



Rear view

*Note :

1. "SS" means Stainless Steel
2. Any special customized, to be confirmed

Item No.	Light source	Lens beam angle(°)	Consumption (watt)	Input Voltage(V)	Ik rate
HE82511*SS/HE82511	1x1W LED	8°/15°/30°/45°/60°	1.2	DC12V DC24V AC100-240V	08
HE82512*SS/HE82512	1x2W LED	8°/15°/30°/45°/60°	2.6	DC12V DC24V AC100-240V	08
HE82516*SS/HE82516	1x3W RGB3in1 LED	30°/45°/60°	3.1	DC12V DC24V	08