Side-emitting inground light

with stainless steel face cover





1E84311/1E84312/1E84316




2E84311/2E84312/2E84316



4E84311/4E84312/4E84316

Outer Dimersions: Unit:mm



Mounting sleeve

Material specifications

Housing:	Outdoor dark grey powder coated aluminum T=60-80um Adhesion of ISO class 1/ASTM class 4B
Front cover:	Hard chrome plate 304# or 316# Stainless Steel
Lens:	Optical lens, efficiency≥85%
Glass:	PMMA diffuser
Glass pressure capacity:	> 1500kgs
Gasket:	Molding shaped silicone seal
Operating temperature:	-20˚C ~ 40˚C
Power cable:	H05RN-F 2×0.75mm² L=0.5m(low voltage) H05RN-F 3×0.75mm² L=0.5m(for Single color/high voltage) H05RN-F 4×0.75mm² L=0.5m(for RGB)
Mounting sleeve:	ABS



***Note:**

1. Item No. with "H" stands for "input voltage AC100-240V"
2. Any special customization, to be confirmed with us

Item No.	Light source	Lens beam angle(˚)	Consumption (watt)	Input Voltage(V)	Ik rate
1E84311(H)/2E84311(H)/ 4E84311(H)	1x1W LED	120°	1.2	DC12V DC24V AC100-240V	10
1E84312(H)/2E84312(H)/ 4E84312(H)	1x2W LED	120°	2.6	DC12V DC24V AC100-240V	10
1E84316/2E84316/4E84316	1x3W RGB3in1 LED	120°	3.1	DC12V DC24V	10