

Strong load-bearing capacity

Driver-over with stainless steel face cover



1E82567




2E82567




4E82567

Outer Dimersions: Unit:mm



Mounting sleeve



Material specifications

Housing:	Outdoor dark grey powder coated aluminum T=60-80um Adhesion of ISO class 1/ASTM class 4B
Front cover:	Hard chrome plate 304# or 316# Stainless Steel
Lens:	Optical lens, efficiency≥85%
Glass:	PMMA diffuser
Glass pressure capacity:	>1800kgs
Gasket:	Molding shaped silicone seal
Operating temperature:	-20˚C ~ 40˚C
Power cable:	H05RN-F 2×0.75mm² L=0.5m(low voltage) H05RN-F 3×0.75mm² L=0.5m(for Single color/high voltage) H05RN-F 4×0.75mm² L=0.5m(for RGB)
Mounting sleeve:	ABS

***Note:**

1. Item No. with "H" stands for "input voltage AC100-240V"
2. Any special customization, to be confirmed with us

Item No.	Light source	Lens beam angle(˚)	Consumption (watt)	Input Voltage(V)	Ik rate
1E82567(H)/2E82567(H)/ 4E82567(H)	1x6WCOB LED	120°	6.5	DC12V DC24V AC100-240V	10
1E825157(H)/2E825157(H)/ 4E825157(H)	OSRAM2835*18pcs	120°	5	DC12V DC24V AC100-240V	10
1E82536/2E82536/4E82536	3x3W RGB3in1 LED	120°	9.1	DC12V DC24V	10